



MUSIC

Professional Natural Music Sound.

model. MKL

เครื่องขยายเสียงเพาเวอร์มิกเซอร์ กำลังวัตต์สูง
 ทรานซิสเตอร์ มีลายน์แม่แมตซึ่งในตัว
 มีเครื่องเล่น USB บันทึกได้, Micro SD, Bluetooth และวิทยุในตัว



MKL-1500W

MKL-2000W

MKL-2500W

MKL-3000W

SPECIFICATION

POWER MIXER AMPLIFIER

| | | |
|-----------------------------|---|------------------------------------|
| TYPE..... | PUBLIC ADDRESS MONO HIGH POWER MIXER AMPLIFIER Built-in MASTER LINE-MATCHING | |
| | FLEX LINE AMPLIFIER built-in USB RECORDABLE / Micro SD / FM TUNER / Bluetooth | |
| INPUT..... | 5 MIC / LINE with SELECTOR SW | IMP. 600Ω / 47kΩ (1/4" PHONE JACK) |
| | 2 AUX with SELECTOR SW | IMP. 47kΩ (RCA JACK) |
| | 1 AUX / USB with SELECTOR SW | IMP. 47kΩ (RCA JACK) |
| INPUT CONTROL..... | CHANNEL VOLUME CONTROL | |
| INPUT TONE CONTROL..... | LOW ~ MID ~ HIGH +/-15dB | |
| INPUT FUNCTION..... | CLIP LED & AUTO MUTE @CHANNEL | |
| | AUTO MUTE FUNCTION (SELECTED CH SOUND LEVEL HAVE REDUCED AUTOMATICALLY | |
| | WHEN NOT SELECTED CH SPEAK) | |
| MASTER CONTROL..... | MASTER VOLUME CONTROL | |
| MASTER TONE CONTROL..... | LOW ~ MID ~ HIGH +/-15dB | |
| MASTER FUNCTION..... | HIGH PASS LF FILTER HORN SWITCH (250Hz CUT OFF) | |
| | INPUT OF POWERAMP PA IN (PHONE JACK), PRE OUT (PHONE JACK) | |
| | RELAY / RECORD OUT (PHONE JACK), SEND & RETURN (PHONE JACK) FOR EFFECT / GEQ | |
| INPUT SENSITIVITY..... | 1V.RMS @ 1kHz AT 4Ω | |
| SIGNAL TO NOISE RATIO..... | BETTER THAN 90dB | |
| FREQUENCY RESPONSE..... | 20Hz ~ 20,000Hz AT +/-3dB | |
| THD + NOISE..... | LESS THAN 0.1% @ 1kHz | |
| OPTION..... | USB RECORDABLE / SD CARD / FM TUNER (81.50MHz - 108.00MHz) / Bluetooth CONNECTION | |
| | BUILT-IN COOLING FAN | |
| | POWER DISPLAY (LINE LED), POWER ON OPERATE LED | |
| | ELECTRONICS SHORT CIRCUIT SPEAKER PROTECTION OUTPUT & LED | |
| | OVERLOAD PROTECTION & LED | |
| RACK HEIGHT..... | 4U RACK HEIGHT | |
| POWER REQUIREMENTS..... | AC 220V ~ 240V / 50Hz ~ 60Hz (FUSE 20A) | |
| OUTPUT..... | SPEAKER 2Ω ~ 8Ω (CONNECT TO TERMINAL - BINDING POST 2P) | |
| | COM ~ 100V ~ 150V ~ 200V (CONNECT TO TERMINAL - BLOCK 4P) | |
| DIMENSIONS (W x H x D)..... | 266mm x 72mm x 245mm | |
| MODEL | POWER OUTPUT AT 2Ω | WEIGHT |
| MKL-1500 | 1500W | 55.2kG |
| MKL-2000 | 2000W | 58.0kG |
| MKL-2500 | 2500W | 61.5kG |
| MKL-3000 | 3000W | 69.5kG |

NOTE : THE SPECIFICATIONS AND DESIGN OF THE PRODUCT ARE SUBJECT TO CHANGE WITHOUT NOTICE DUE TO IMPROVEMENT